



Systemabdichtungsbaustoffe

KAUBIT CHEMIE Aktiengesellschaft • Industriestraße 1 • 49413 Dinklage  
Telephone: +49 4443 9669-0 • Telefax: +49 4443 9669-66 • Internet: www.kaubit.de • E-Mail: info@kaubit.de

## Kaubiflex FA Floor packing

## Technical datasheet

Edition 12.04.2007

**Elastic packing for a permanent sealing of floor drains in combination with sealing systems under ceramic coverings.**

### Properties:

Kaubiflex FA Floor Packing is watertight, permanently elastic sealing. The packing is made from a compound based on polymeric dispersion with a centrally inserted fabric layer. This material basis causes an excellent bonding with almost any waterproofing materials used under tiles extending over the entire surface of the packing.

### Applications:

Kaubiflex FA Floor Packing is used to permanently waterproof ground drains. The packing is complete embedded into the sealing compound.

### Technical specifications:

Colour:	grey
Moisture vapour transmission resistance coefficient:	1500 $\mu$
Equivalent air thickness $S_d$ :	0.9 m
Elongation:	57 %
Thickness:	appr. 0.6 mm

When exposed for a short time Kaubiflex FA Floor Packing is resistant to most of diluted acids and lyes as well as to fuel oil and gaze. Kaubiflex FA Floor Packing is stable under temperatures from -20°C to + 70°C .

### Measurements:

350 x 350 mm  
400 x 400 mm

### Preparation of the substrate:

The preparation of the surface depends on the respective waterproofing system used.

### Use:

The Kaubiflex FA Floor Packing is put over the drain passage, laid and pressed into the fresh sealing mass. When applying the second coating with the sealing mass the entire packing is coated as well. When the waterproofing system has to be applied in one coat the packing is laid into a previously applied thin layer of the system before the system is applied over the whole area. The required hole for the ground drain has to be made beforehand as per requirement at site.



### Information on further processing:

Kaubiflex FA Floor Packing is absolutely silicone-compatible; a soaking must not be expected. For lining the joints usual silicones may be applied. Solvent-free adhesives and coatings may be applied directly onto the Kaubiflex FA Floor Packing. Before applying further products a compatibility test has to be carried out.

### Cleaning of tools and equipment:

Tools and soiled areas should be cleaned immediately after use with water.

### Storage:

Kaubiflex FA Floor Packing can be used for a period of at least 12 months when stored in a cool and dry period.

### Supplied as:

1 and 5 pieces / carton

### Safety information:

The product is not hazardous as defined in the (German) Hazardous Substances Code.

### Disposal:

Packing can be recycled under the "Green Dot" scheme operated by Duales System Deutschland AG.

**For further information, see the Health and Safety sheet.**